



## ISO-Sealing tape S

---

### **Uses:**

ISO-Sealing Tape S sticks and seals reliably tears, wall connections and elastic expansion joints. Preferential areas of application are bathroom units and sanitary rooms. Easily plastering and tiling is possible through the outside covered fleece.

### **Technical data:**

ISO- Sealing tape S is a self-adhesive cold applied sealing tape.  
ISO- Sealing tape S is elastic.

Area-related mass:	ca. 1,5 kg/m <sup>2</sup>
Complete tape thickness:	ca. 1,5 mm
Color:	Covering: black Fleece: white

### **Application:**

The surfaces to be sealed have to be dry. Free from frost, grease and silicone as well as abrasion-proof. Porous and dusty subsoil should be pre-treated with primer (ca. 200ml/m<sup>2</sup>) to achieve an optimum adhesion.

If ISO- Sealing tape S is put on it has to be pressed strong.

It must be fixed loops-shaped if expansion joint can be existing.

### **Standard – form of supply:**

Length/roll:	10 m
Roll width (mm):	100
Rolls/carton:	3
Carton/pallet:	96

Recommended primers:	COLZUMIX®-Haftgrund Baumuls V-SK
----------------------	-------------------------------------

Packing size:	1 l
---------------	-----

### **Storage:**

protected from direct sunlight, dry and standing on its cutting edge