



ISO- Spike sealing tape DSK

Uses:

ISO-Repair Tape AL bonds and seals reliably metal, plastics, concrete, masonry, plaster, wood and glass. It is especially suited for the sealing of

joints and cracks,
rain gutters,
connections to roof and wall,
covers,
glass roofs and greenhouses,
steel constructions,
roofing systems, eaves and valley flashing

Application:

The surfaces to be sealed have to be dry. Free from frost, grease and silicone as well as abrasion-proof. Porous and dusty subsoil should be pre-treated with primer (ca. 200ml/m²) to achieve an optimum adhesion.

The best application temperature range is between 5°C and 45°C air or surface temperature. At lower temperatures the coating compound can be tempered with the help of a propane flame or a hot air unit (attention: safety requirements have to be observed).

The Inside coated foil must be removed partial, as for the joint plane is needed. Afterwards spike sealing tape DSK will be stick on by pressing strong on the paper side with hands or using a pressing roll.

The appearance of cavities (blisters) has to be avoided.

If it is not required to use the second available adhesive tape side, it can be covered with grit.

Walkable or rolled subsoil are not suitable for the application.

Technical data:

ISO spike sealing tape DSK is a self-adhesive cold applied sealing tape. This coating compound consists of elastomer bitumen and high quality adhesive resins, which are protected by a silicone coated foil.

Area-related mass:	ca.2,2 kg/m ²	
Complete tape thickness:	2,0 mm	
Building material class:	B 2, normal inflammable	DIN 410
Softening point:	>95 °C	DIN 52011
Cold bending behaviour:	> - 40 °C	DIN 52 123
Temperature resistance:	- 30 °C to + ca. 80°C	



Standard – form of supply:

Roll width (mm):	50	60	100
Rolls/carton:	6	6	6
Length/Roll (m):	10	10	10

Other packing units are possible on inquiry.

Recommended primers: COLZUMIX®-Haftgrund
Packing size: 1 l

Storage:

The product should be protected from direct sunlight and be stored at 10 °C to 30 °C. Furthermore the rolls stored dry and standing on its cutting edge. The product is not endangered by frost.

The properties of ISO- spike sealing tape DSK stay unchanged for a long time.